



Material Safety Data Sheet

Section 1: Product and Company Identification

RPM Wood Finishes Group, Inc.

P.O. Box 22000

Hickory, NC 28603

Company Phone number: (800) 522-8266

CHEMTREC: (800) 424-9300 International: 703-527-3887 (collect)

EHS Review/Issue Date: 12/20/2011

Product Name: TONE FINISH MED RED /SHADING MAHOGANY
Product Code: M101-0386

Section 2: Hazards Identification

EMERGENCY OVERVIEW

Appearance: Colored Liquid

Odor: Moderately Strong Alcohol

Principal Hazards: DANGER! Extremely Flammable.

Causes eye, skin, nose and throat irritation. Harmful or fatal if swallowed. Harmful if inhaled. Vapor harmful.

Potential Health Effects: See Section 11 for more information.

Primary Routes of Exposure:

Eye Contact:

Product may cause eye damage; signs and symptoms may include burns, vision impairment, permanent corneal damage and/or soft tissue damage.

Ingestion:

Product if ingested may cause damage (including burns, scarring, and ulcerization) to mouth, throat, stomach, and digestive and central nervous systems. Signs and symptoms may include headache, drowsiness, dizziness, swelling, abdominal discomfort, burning sensation, shock or collapse, convulsions and/or bleeding. Post-ingestion vomitous in the lungs may cause chemical pneumonia.

Skin Contact:

Product may cause skin damage; signs and symptoms may include blistering, burns and/or possible scarring.

Inhalation:

Product if inhaled may cause severe irritation or damage (including but not limited to burns, scarring, and ulcerization) to respiratory tract and central nervous system. Signs and symptoms may include weakness, headache, drowsiness, dizziness, swelling, abdominal discomfort, burning sensation, shock or collapse, convulsions, breathing difficulties, nasal perforation, ulceration, heart damage, blindness, bleeding and/or death. Serious risk of suffocation when in confined area. NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

Material Safety Data Sheet

Product Name: TONE FINISH MED RED /SHADING MAHOGANY

Target Organs: Not Determined

Carcinogenicity: This product contains carcinogens or potential carcinogens as listed by IARC or NTP.

Hazardous Listing: Components of this product are considered hazardous per the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Section 3: Composition/Information on Ingredients

Chemical	CAS	Percent Composition
acetone	67-64-1	20 - 30
propane	74-98-6	10 - 20
isobutyl acetate	110-19-0	1 - 10
ethyl acetate	141-78-6	1 - 10
n-butyl acetate	123-86-4	1 - 10
isobutane	75-28-5	1 - 10
ethanol	64-17-5	1 - 10
toluene	108-88-3	1 - 10
cellulose nitrate, cellulose ester	9004-70-0	1 - 10
alkyd resin	proprietary NCP	1 - 10
isopropanol	67-63-0	1 - 10
isobutyl isobutyrate	97-85-8	1 - 10
2,2,4-trimethyl-1,3-pentanediol diisobutyrate	6846-50-0	< 1
butyl cellosolve	111-76-2	< 1
m-xylene	108-38-3	< 1
iron oxide red	1332-37-2	< 1
amorphous fumed silica	68611-44-9	< 1
castor oil	8001-79-4	< 1
o-xylene	95-47-6	< 1
pm acetate	108-65-6	< 1
ethylbenzene	100-41-4	< 1
p-xylene	106-42-3	< 1
isopropyl acetate	108-21-4	< 0.1
acrylic resin	proprietary	< 0.1
wax solids	proprietary	< 0.1

Section 4: First Aid Measures

Eye Contact:

If exposure occurs, flush the affected eye for at least 20 minutes. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Seek medical attention immediately after flushing.

Material Safety Data Sheet

Product Name: TONE FINISH MED RED /SHADING MAHOGANY

Ingestion:

Do not induce vomiting. Dilute with water or milk. Never give fluids if the victim is unconscious or having convulsions. Seek medical attention immediately. Contact Poison Control Center immediately.

Skin Contact:

If exposure occurs, flush the affected area thoroughly with water for at least 15 minutes. Destroy contaminated clothing and shoes. Seek medical attention immediately.

Inhalation:

Remove to fresh air. If not breathing, administer CPR until help arrives or the victim starts to breathe on his own. If breathing is difficult, give oxygen. Seek medical attention immediately.

Section 5: Fire Fighting Measures

Extinguishing Media:

Use alcohol foam, dry chemical, carbon dioxide or any Class B fire extinguishing agent. Water may be unsuitable for extinguishing fires. Water may be used to cool and prevent the rupture of containers that are exposed to the heat from a fire.

Products of Combustion:

Protection of Firefighters / Explosion Hazards:

Evacuate all persons from the fire area to a safe location. Move non-burning material, as feasible, to a safe location as soon as possible. Fire fighters should be protected from potential explosion hazards while extinguishing the fire. Wear self-contained breathing apparatus (SCBA) and full fire-fighting protective clothing. Thoroughly decontaminate all protective equipment after use. Containers of this material may build up pressure if exposed to heat (fire). Use water spray to cool fire-exposed containers. Use water spray to disperse vapors if a spill or leak has not ignited. DO NOT extinguish a fire resulting from the flow of flammable liquid until the flow of the liquid is effectively shut off. This precaution will help prevent the accumulation of an explosive vapor-air mixture after the initial fire is extinguished.

Section 6: Accidental Release Measures

Material Safety Data Sheet

Product Name: TONE FINISH MED RED /SHADING MAHOGANY

Section 7: Handling and Storage

Handling:

Contents under pressure. Do not puncture, incinerate, or discard in a compactor. Do not store above 120°F, or in direct sunlight. Intentional misuse by deliberately concentrating and inhaling vapors may be harmful or fatal.

Storage:

Section 8: Exposure / Personal Protection

OSHA 29 CFR 1910.1000 Air Contaminants – Tables:

Chemical	CAS	Z-1 PEL (units as noted)	Z-2 PEL (PPM)	Z-3 Status	Specifically Regulated see:	ACGIH TLV (units as noted)
acetone	67-64-1	2400 MGM3 (1000 PPM)				500 PPM
propane	74-98-6	1800 MGM3 (1000 PPM)				
isobutyl acetate	110-19-0	700 MGM3 (150 PPM)				150 PPM
ethyl acetate	141-78-6	1400 MGM3 (400 PPM)				400 PPM
n-butyl acetate	123-86-4	710 MGM3 (150 PPM)				150 PPM
isobutane	75-28-5					1000 PPM
ethanol	64-17-5	1900 MGM3 (1000 PPM)				1000 PPM
toluene	108-88-3		200 PPM			20 PPM
cellulose nitrate, cellulose ester	9004-70-0					
alkyd resin	proprietary NCP					
isopropanol	67-63-0	980 MGM3 (400 PPM)				200 PPM
isobutyl isobutyrate	97-85-8					
2,2,4-trimethyl-1,3-pentanediol diisobutyrate	6846-50-0					
butyl cellosolve	111-76-2	240 MGM3 (50 PPM)				20 PPM
m-xylene	108-38-3	435 MGM3 (100 PPM)				100 PPM
iron oxide red	1332-37-2					
amorphous fumed silica	68611-44-9					
castor oil	8001-79-4					
o-xylene	95-47-6	435 MGM3 (100 PPM)				100 PPM
pm acetate	108-65-6					
ethylbenzene	100-41-4	435 MGM3 (100 PPM)				100 PPM
p-xylene	106-42-3	435 MGM3 (100 PPM)				100 PPM
isopropyl acetate	108-21-4	950 MGM3 (250 PPM)				100 PPM
acrylic resin	proprietary					
wax solids	proprietary					

Material Safety Data Sheet

Product Name: TONE FINISH MED RED /SHADING MAHOGANY

Engineering Controls:

Eye / Face Protection:

Skin Protection:

Respiratory Protection:

A NIOSH-approved air-purifying respirator with the appropriate cartridge may be appropriate under certain circumstances where airborne concentrations are expected to exceed permissible exposure limits. Protection provided by air-purifying respirators is limited. Use a positive-pressure, air supplied respirator if there is potential for an uncontrolled release, exposure levels are not known or any other circumstances where air-purifying respirators may not provide adequate protection.

General Hygiene Considerations:

Section 9: Physical and Chemical Properties

Physical State:	Colored Liquid
Odor:	Moderately Strong Alcohol
Odor Threshold:	Not determined.
pH:	Not determined.
Freezing Point:	Not determined.
Boiling Point:	Not determined.
Flash Point (°F):	-144 (CALC.)
Evaporation Rate:	Not determined.
Flammability (solid, gas):	Not determined.
Upper Flammability Limit:	Not determined.
Lower Flammability Limit:	Not determined.
Vapor Pressure:	Not determined.
Vapor Density:	Not determined.

Material Safety Data Sheet

Product Name: TONE FINISH MED RED /SHADING MAHOGANY

Specific Gravity:	0.77
Weight per Gallon (lbs):	6.39
Solubility (water):	Not determined.
Partition Coefficient (n-octanol/water):	Not determined.
Auto-ignition Temperature:	Not determined.
Coating VOC g/l:	659.93
Coating VOC lbs/gal:	5.5
Material VOC g/l:	499.17
Material VOC lbs/gal:	4.16
Solids VOL%:	5.47
Solids WT %:	9.65

Contains Non-Photochemically Reactive Solvent.

VOC data per US EPA guidelines. Some states and localities have guidelines more stringent than federal regulations.

Aerosol coating product category codes and applicable reactivity limits are displayed on product labels per 40 CFR 59.507.

Section 10: Stability and Reactivity

Stability:

Conditions to Avoid/Incompatible Materials:

Hazardous Decomposition Products:

Material Safety Data Sheet

Product Name: TONE FINISH MED RED /SHADING MAHOAGANY

Section 11: Toxicology Information

Chemical	CAS	IARC	NTP
acetone	67-64-1		
propane	74-98-6		
isobutyl acetate	110-19-0		
ethyl acetate	141-78-6		
n-butyl acetate	123-86-4		
isobutane	75-28-5		
ethanol	64-17-5	*	*
toluene	108-88-3		
cellulose nitrate, cellulose ester	9004-70-0		
alkyd resin	proprietary NCP		
isopropanol	67-63-0		
isobutyl isobutyrate	97-85-8		
2,2,4-trimethyl-1,3-pentanediol diisobutyrate	6846-50-0		
butyl cellosolve	111-76-2		
m-xylene	108-38-3		
iron oxide red	1332-37-2		
amorphous fumed silica	68611-44-9		
castor oil	8001-79-4		
o-xylene	95-47-6		
pm acetate	108-65-6		
ethylbenzene	100-41-4		
p-xylene	106-42-3		
isopropyl acetate	108-21-4		
acrylic resin	proprietary		
wax solids	proprietary		

Toxicological evaluation of this product as a whole has not been performed. Individual components that are potential or known carcinogens are listed above.

Section 12: Ecological Information

Material Safety Data Sheet

Product Name: TONE FINISH MED RED /SHADING MAHOGANY

Section 13: Disposal Considerations

Section 14: Transportation Information

DOT Basic description: UN1950, AEROSOLS, FLAMMABLE, 2.1

See 49 CFR 172.101 for Special Provisions, Packaging, and Quantity Limitations.

Section 15: Regulatory Information

Chemical Name	CAS	CERCLA	CERCLA RQ	EPCRA EHS	EPCRA TPQ	SARA 313	TSCA	DSL	EINECS	Proposition 65	WHMIS
acetone	67-64-1	*	5000 LBS				*	*	*		*
propane	74-98-6						*	*	*		
isobutyl acetate	110-19-0	*	5000 LBS				*	*	*		*
ethyl acetate	141-78-6	*	5000 LBS				*	*	*		*
n-butyl acetate	123-86-4	*	5000 LBS				*	*	*		*
isobutane	75-28-5						*	*	*		
ethanol	64-17-5	*	100 LBS				*	*	*	*	*
toluene	108-88-3	*	1000 LBS			*	*	*	*	*	*
cellulose nitrate, cellulose ester	9004-70-0	*	100 LBS				*	*			
alkyd resin	proprietary NCP										
isopropanol	67-63-0					*	*	*	*		*
isobutyl isobutyrate	97-85-8						*	*	*		
2,2,4-trimethyl-1,3-pentanediol diisobutyrate	6846-50-0						*	*	*		
butyl cellosolve	111-76-2						*	*	*		*
m-xylene	108-38-3	*	1000 LBS			*	*	*	*		*
iron oxide red	1332-37-2						*	*	*		
amorphous fumed silica	68611-44-9						*	*	*		
castor oil	8001-79-4						*	*	*		*
o-xylene	95-47-6	*	1000 LBS			*	*	*	*		*
pm acetate	108-65-6						*	*	*		
ethylbenzene	100-41-4	*	1000 LBS			*	*	*	*	*	*
p-xylene	106-42-3	*	100 LBS			*	*	*	*		*
isopropyl acetate	108-21-4						*	*	*		*
acrylic resin	proprietary										
wax solids	proprietary										

WARNING: This product contains a chemical known to the state of California to cause cancer and birth defects, or other reproductive harm.

Material Safety Data Sheet

Product Name: TONE FINISH MED RED /SHADING MAHOGANY

Section 16: Other Information

HMIS Codes Health 2 Flammability 4 Reactivity 0

Key to Abbreviations:

*	Item appears on indicated list (or inventory)
ACGIH	American Conference of Governmental Industrial Hygienists
CAS	Chemical Abstract Service Registry Number
CERCLA	Comprehensive Environmental Response, Compensation, and Liability Act
CERCLA RQ	CERCLA Reportable Quantity
CFR	Code of Federal Regulations
CPR	Cardiopulmonary resuscitation
DSL	Domestic Substances List of Canada
EINECS	European Inventory of Existing Chemical Substances
EPCRA	Emergency Planning and Community Right-to-know Act
EPCRA EHS	EPCRA Extremely Hazardous Substance
EPCRA TPQ	EPCRA Threshold Planning Quantity
°F	Fahrenheit degrees
g/l	Grams per liter
gal	Gallons
IARC	International Agency for Research on Cancer
lbs or LBS	Pounds
MGM3	Milligrams per cubic meter
MIR	Maximum Incremental Reactivity
MSDS	Material Safety Data Sheet
NCP	WHMIS Non-Controlled Product
NIOSH	National Institute of Occupational Safety and Health
NTP	National Toxicology Program
OSHA	Occupational Safety and Health Administration
PEL	Permissible Exposure Limit
PPM	Parts per million
Proposition 65	California's Safe Drinking Water and Toxic Enforcement Act
SARA	Superfund Amendments and Reauthorization Act
TLV	Threshold Limit Value
TSCA	Toxic Substances Control Act
USEPA	United States Environmental Protection Agency
VOC	Volatile Organic Compound
VOL	Volume
WT	Weight
WHMIS	Canadian Workplace Hazardous Materials Information System
UN	United Nations